



STT Defu 1

STT Defu 2

STT DEFU 2

Joining STT Defu 1 to form STT GDC's flagship data centre campus, STT Defu 2 will enable customers to scale easily in today's highly digitised world. The upcoming data centre will also be outfitted with numerous solutions to enable connectivity within the campus, to other STT GDC data centres, leading carrier hotels and top public cloud platforms.

BUILDING OVERVIEW

Purpose-built five storey building with reinforced concrete super-structure

Location	23 Defu Avenue 1, Singapore 539541
Gross Floor Area	150,010 sqft (14,400.97sqm)
Net Lettable Area	55,145 sqft (5,120sqm)
Flight Path	No
Slab-to-slab Height	Up to 5.95m
Floor Loading	Up to 15KN/m ²
Loading Bays	2
Staging Room	1
Passenger Lifts (1,360kg)	2
Cargo Lift (5,000kg)	1
Service Lift (2,000kg)	1

FIRE DETECTION AND SUPPRESSION SYSTEM

VESDA

Pre-Action Sprinkler System and Gas Suppression System (NOVEC)

2hr fire-rated doors and partitions

24x7 decentralised fire alarm monitoring system (DECAM) that links directly to an external fire monitoring agency

POWER

2 diverse and redundant 22kV utility power supplies and sub-stations

Up to 12MW of IT Load

2N Diesel Rotary Uninterrupted Power Supply (DRUPS)

Concurrently maintainable

Fault tolerant

Separate essential source backup generator

Underground fuel tank providing up to 36hrs of support at full load

CONNECTIVITY

Carrier-neutral

2N main distribution frame (MDF) room

2N meet-me-room (MMR)

2N diverse fibre point of entry to site

Access to multiple carriers, internet service and cloud service providers

CONTACT

E info@sttelemediagdc.com **W** sttelemediagdc.com

All information contained in this factsheet ("Information") is for information purposes only, and is not intended to constitute an offer or contract of any kind. STT GDC does not warrant the accuracy, adequacy or completeness of the Information and expressly disclaims all liabilities relating to the Information. STT GDC shall in no event be liable for any damages, loss or expense however caused arising from, or in connection with, the use of, or reliance on, the Information. No Information or parts of it may be reproduced, distributed, modified or displayed without the prior written permission of STT GDC. © 2018 STT GDC Pte Ltd (CRN: 201228542D).

COOLING

Design PUE of 1.4

2N resilient Chilled Water Plant with 2N Cooling Towers

- Designed with Chill Water Storage/Buffer Tank catering continuous cooling at full load during power failure (min. 5 mins)

- Oversized pipework to reduce pumping energy for efficiency

- Fault tolerant and no risk of contamination in 1 system impacting other

2N diverse chilled water piping loops

Service corridor with dual coil CRAC with 2N power supply of up to N + 25% resiliencies

Backup Water System: 2 x 300,000 litre make-up water tanks (also used for fire suppression)

Domestic water supply with make-up water system and NEWater pipeworks readiness

SECURITY

Anti-crash boundary wall with perimeter protection against vehicle-borne improvised explosive device (VBIED)

Perimeter wall with BRC fencing and barb mesh

Anti-climb fencing at front gate

Comprehensive intrusion detection

K12 rated vehicle crash barriers

24x7 CCTV recording at 1080p resolution, fixed with pan-tilt-zoom (PTZ) video analytics and kept for 90 days

Perimeter surveillance with day and night cameras fixed with Pan-Tilt-Zoom (PTZ) Video Content Analytics (loitering and abandoned object detection)

24x7 on-site manned guards

24x7 controlled site access with 2-factor authentication by pre-authorisation

Contactless card access system with RFID real-time movement tracking within building and biometric access control system

CERTIFICATIONS

LEED Gold

TIA 942-B Rated-4

SS564

ISO 27001

BCA-IMDA Green Mark Platinum (New Data Centres V1.1)

PCI DSS

BCA-IMDA Green Mark Platinum

SOC 2 Type II
